



# HUMBOLDT

## H-1431 Asphalt Solvent Recycler



H-1431

### Asphalt Solvent Recycler

This unit has been designed to recycle the solvents used in asphalt extraction tests. It successfully extracts pure solvent from the oil and wastes generated from the extraction process and generates clean solvent ready for reuse in a new test. The unit reduces the need for new solvent and eliminates problems with solvent disposal.

- UL 2208 Certified
- 6 gallon heavy-duty stainless steel boiling tank
- Air-cooled, no water hook-up necessary
- Bag-lined tank allows easy removal of solid contaminants
- Vacuum-assist option for higher boiling solvents
- Quiet operation and low maintenance
- Multiple safety controls with automatic shutoffs
- Mobile – mounted on locking wheels for easy relocation & stabilizer bars for added support
- Easy installation to standard connection: 220/240V or 120V
- Electric fill pump available as an option
- Small footprint – 22.25" w x 39" l x 44" h

Operating capacity:	6 gallons / 23 Liters
Voltage:	120V 60Hz or 240V 60HZ
Wattage:	2800 VA (240V) 2300 VA (120V)
Maximum Rated Load:	11.1 A (240V) or 185 A (120V)
Voltage:	120V 60Hz or 240V 60Hz
Net weight:	290 lbs (132kg)

# Asphalt Solvent Recycler



**Humboldt Mfg. Co.**  
**[www.humboldtmfg.com](http://www.humboldtmfg.com)**  
875 Tollgate Road  
Elgin, Illinois 60123 U.S.A.

U.S.A. Toll Free: 1.800.544.7220  
Voice: 1.708.468.6300  
Fax: 1.708.456.0137  
email: [hmc@humboldtmfg.com](mailto:hmc@humboldtmfg.com)